BT0104 SPECIFICATIONS

metrix·2 blu·stone™ freestanding bathtub

FEATURES:

- Freestanding or alcove blu·stone™ bathtub
- Alcove installation requires separate tile flange, not included (Blu recommends TF.BTSB tile flange)
- Streamlined, low profile one piece design for showering convenience
- 591/2" (1512mm) L x 30" (762mm) W x 18" (460mm) H
- Suitable for left or right hand drain installation
- Includes integral slot overflow & matching blu·stone $^{\scriptscriptstyle\mathsf{TM}}$ waste cover
- Made of blu·stone™ providing the look and feel of natural stone
- Stronger and more durable than acrylic
- Non-porous, stain resistant surface that does not require sealing
- Does not promote bacteria, mold or fungi
- Ultra deep bathing well for compact foot-print
- Tailpiece not included (Blu recommends BTWaste.RN or BTWasteCl.RN)

SPECIFICATIONS:

Basin Area: 48" (1218mm) x 26" (662mm)*

Top Area: 54" (1372mm) x 28" (712mm)*

To Overflow: 21/4" (60mm)*

Water Depth: 133/4" (350mm)*

Slope of Backrest: 74°/87°*

Capacity: 82G (310L)

Weight: 410lbs (186kg)

Hot water supply reg'd: Should be 70% of water

capacity of tub or greater

Warranty: Five Year Warranty (Residential use)

One Year Warranty (Commercial use)

Material: blu·stone™ Shipping Weight: 542lbs (246kg)³

Shipping Dimensions: (LWH) 621/4" x 323/4" x 191/4"

(1582mm x 832mm x 490mm)*

FINISHES:

White Matte as standard

Gloss finish & custom colors available (Tier 1/Custom)

ACCESSORIES

- TF.BTSB tile flange for alcove installation
- BTWaste.RN or BTWasteCl.RN Island tub drain for easy installation

INSTALLATION NOTES:

Install this product according to the installation guide. Floor support under bath must provide for a minimum of 1600 lbs (725kg). Installation will vary. Our products must be installed by certified professionals only and according to our installation guide as well as federal, provincial / state and local building codes and regulations

CODES / STANDARDS APPLICABLE:

- Meets or exceeds ANSI / ASME standard CSA B45.5.11 / IAPMO Z124
- IAPMO / ANSI Z124.8
- CSA





*Approximate measurements for comparison only.

Note: These dimensions and specifications are subject to change without notice.











