

**4.8LPF / 1.28GPF OR 3LPF / 0.8GPF**

**4720BLWU**

### Unlined Tank with Bowl

## PRODUCT SPECS

- High efficiency dual flush toilet
- 4.8Lpf / 1.28Gpf or 3Lpf / 0.8Gpf
- Elongated bowl
- Vitreous china
- 15½" Bowl height
- Soft white top push button
- 12" (305mm) Rough-in
- 1¾" Fully glazed ball pass trapway
- 3" Dual flush valve
- Siphon jet flush action
- Water Surface: 8" x 6" (205mm x 150mm)
- Toilet seat not included

## COMPLIANCE CERTIFICATIONS

Meets or exceeds the following:

- IAPMO cUPC
- US EPA WaterSense
- ASME A112.19.2 / CSA B45.1
- MaP Premium Tested 800g
- LEED Compliant

## SHIPPING

Cube 6.41

GW 86.59 lbs



## DIMENSIONS

440mm W x 743mm D x 803mm H

17<sup>3</sup>/<sub>8</sub>" W x 29<sup>1</sup>/<sub>4</sub>" D x 31<sup>5</sup>/<sub>8</sub>" H

**TO BE SPECIFIED**

Colour:

■ Soft White

**NOTES:** This toilet is designed to rough-in at a minimum dimension of 305mm (12") from finished wall to C/L of outlet. Supply line not included with fixture and must be ordered separately.

Important: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ASME standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

