

CARLTON URINAL

1.9Lpf / 0.5GPF | WALL MOUNTED

□ 4810BFX

Top Inlet

PRODUCT SPECS

- High efficiency urinal
- 1.9Lpf / 0.5Gpf
- Vitreous china
- Washout flush action
- 3/4" Top inlet spud
- Outlet connection threaded 2" inside NPTF
- Flushing rim
- Extended sides for privacy
- Integral trap
- Elongated 14 3/4" rim from finished wall
- For concealed carrier installation
- Includes vitreous china strainer
- Flushometer not included

DIMENSIONS

445mm W x 375mm D x 684mm H

17 1/2" W x 14 3/4" D x 27" H

COMPLIANCE CERTIFICATIONS

Meets or exceeds the following:

- IAPMO cUPC
- US EPA WaterSense
Please note: In order to comply with WaterSense certification this urinal must be used with 1.9Lpf / 0.5Gpf WaterSense labeled flushometer.
- ASME A112.19.2 / CSA B45.1
- LEED Compliant

SHIPPING

Cube 5.27

GW 65 lbs



TO BE SPECIFIED

Colour:

- Soft White

NOTES: Flush Valve is not included and must be ordered separately. Provide suitable reinforcement for all wall supports. Important: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ASME standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

Complies with ADA Section 4.18 when installed per code.

