

CATO TWO PIECE TOILET

3.5LPF / 0.92GPF

□ 5730BEXU

Unlined Tank with bowl

PRODUCT SPECS

- High efficiency toilet
- 3.5Lpf / 0.92Gpf
- Elongated bowl
- Vitreous china
- 15½" Bowl height
- Soft white tank lever
- 12" (305mm) Rough-in
- 1¾" Fully glazed ball pass trapway
- 3" Flapper
- Siphon jet flush action
- Water surface: 8" x 6" (205mm x 150mm)
- Toilet seat not included

COMPLIANCE CERTIFICATIONS

- Meets or exceeds the following:
- IAPMO cUPC
 - US EPA WaterSense
 - ASME A112.19.2 / CSA B45.1
 - MaP Premium Tested 600g
 - LEED Compliant
 - CSA B651

SHIPPING

Cube 6.54
GW 92lbs

DIMENSIONS

440mm W x 744mm D x 803mm H

17¼" W x 29¼" D x 31½" H



TO BE SPECIFIED

Colour:

- Soft White

NOTES: This toilet is designed to rough-in at a minimum dimension of 305mm (12") from finished wall to C/L of outlet. Supply line not included with fixture and must be ordered separately.

Important: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ASME standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

Products are designed to comply CSA B651 Standard. It shall be the responsibility of the installer to comply with the local disability codes and standards prior to installing the product.

For additional component options and specifications, please visit contrac.ca / contrac.us

