



Swanstone Crystal Colors Overlap Shower Wall Panel

Manufactured from Swanstone solid surface
(See page 2 for detailed information.)

Recommended for high-use traffic areas and commercial surfaces.

WARRANTY
Limited Lifetime – Residential
Limited 25-year – Commercial

FEATURES

- Reinforced solid surface means color and texture run all the way through and cannot wear away.
- Will not mold or mildew, no grout to clean.
- Ideal for remodeling, panels glue up over existing surface.
- Coordinates with other Swanstone bath products.
- Can be easily trimmed to fit any shower application.
- Widest range of sizes to fit most any project.
- Heat resistant—walls can handle steamer units.
- Compression molding means superior durability.



NOTE: Overlap panels are used to create 60 x 36 x 72-inch or 60 x 36 x 96-inch enclosure combined with CCSK72-3648 or CCSK96-3648.

Overlap Panel Shower Walls

11-3/4" wide x 72" high (298 mm x 1829 mm)

11-3/4" wide x 96" high (298 mm x 2438 mm)

SPECIFICATIONS

Swanstone Crystal Colors Overlap Shower Wall Panel

Model	Part	Nominal Dimensions	Ship Wt. Lb.	Ship FedEx	Carton Dims. In.	Cu. Ft.
CCSO-1272	CCSO01272	11-3/4" W x 72" H	23	—	74 x 14 x 2	1.199
CCSO-1296	CCSO01296	11-3/4" W x 96" H	23	—	98 x 14 x 2	1.59

Kit Includes: One flat wall panel. It may be necessary to combine cartons to accommodate desired installation area. No installation materials provided.

Packaging: Each kit is packed in an individual carton.

COLORS

- Caramel Glass (133)
- Crystal Black (107)
- Crystal Cream (106)
- Crystal White (105)
- Gray Glass (134)
- Ivory Glass (132)

ACCESSORIES

- CCSS-1125 Crystal Colors Corner Soap Shelf

STANDARDS AND RATINGS

American Society of Testing and Materials (ASTM) E-84: Class A Flame Spread Rating

American National Standard Institute—ANSI Z124.6

International Association of Plumbing and Mechanical Officials (IAPMO)—Listed

cUPC listed—Certified to CSA Test Standard B45.5 by IAPMO

Uniform Plumbing Code (UPC)

For a complete list of tests and results see the Technical Data Sheet.

SUPPORT DOCUMENTS

Installation instructions available at swanstone.com.

MAINTENANCE AND CLEANING INFORMATION

Clean regularly with common household liquid cleaners and rinse within five minutes of application. Occasional scrubbing with abrasive cleaners ensures that the original luster will be maintained. **Do not** use "leave on" cleaning products, such as automatic spray shower cleaners. Prolonged contact with harsh chemicals could have an adverse reaction over time and discolor surfaces.

Do not use cleaning agents that caution use on acrylic, polyester or plastics.

